

linea xs inground hp

pureWhite

TECHNICAL DATASHEET

linea xs inground hp

pureWhite

Technical Data

Dimensions 46 mm x 74 mm [W x H]
1.81 in x 2.91 in [W x H]

Installation housing:
50 mm x 130 mm [W x H]
1.97 in x 5.12 in [W x H]

Standard Unit Lengths 629 mm, 934 mm, 1239 mm
24.77 in, 36.78 in, 48.78 in

Fixture Typ



pureWhite

Color Temperatures pureWhite 2200 K, 2700 K, 3000 K, 3500 K, 4000 K, 6500 K
* Project-specific color temperature for pureWhite available.

Beam Angles 8°, 10°, 23°, 43°, 8° x 31°
10° x 42°, 12° x 60°, 14° x 100°, 30° x 60°, 60° x 30°

Luminous Flux 629 mm (24.77 in): 1758 lm
934 mm (36.78 in): 2637 lm
1239 mm (48.78 in): 3516 lm

Light Source 629 mm (24.77 in): 16 LEDs
934 mm (36.78 in): 24 LEDs
1239 mm (48.78 in): 32 LEDs

Color Rendering Index $R_a \geq 80$

Antiglare optional:







- Hex louver (internal)
- Linear louver (internal)

LED-Binning













MacAdam Ellipses Binning 3


Dimming Non-dimmable | Dimmable (DALI, 0 - 10 V, DMX)

Input Voltage	Power supply: external 36 VDC EXT: Constant current, max. 500 mA
Power Consumption	629 mm (24.77 in): Max. 28 W 934 mm (36.78 in): Max. 42 W 1239 mm (48.78 in): Max. 56 W
Protection Class	II
Storage Temperatur	-40 °C / +80 °C -40 °F / +176 °F
Operating Temperature	-40 °C / +40 °C -40 °F / +104 °F
Start-up Temperature	-25 °C / +40 °C -13 °F / +104 °F
Lumen Maintenance [L70]	65'000 h @ 25 °C (77 °F) 40'000 h @ 40 °C (104 °F)
Housing	Aluminum extruded profile
Housing Color(s)	 Black anodized
Lens	Tempered safety glass, extra white
Ingress Protection	IP67
Environment	 indoor  outdoor
Impact Protection	IK09
Certification	  

Beam Angles



Engineering Drawing



Project	Fixture#	Date
		Firm

Ordering Information

Choose the option that suits your needs and write its corresponding code on the appropriate line to form the product code.

LIN-XS-IN-HP- _____ - _____ - _____ - _____ - _____ - Y01

TYP - LUMINOUS COLOR
DIMMING
FIXTURE LENGTH
BEAM ANGLE
GLARE PROTECTION

TYP - LUMINOUS COLOR	
PW22	pureWhite - 2200 K
PW27	pureWhite - 2700 K
PW30	pureWhite - 3000 K
PW35	pureWhite - 3500 K
PW40	pureWhite - 4000 K
PW65	pureWhite - 6500 K

BEAM ANGLE	
8X8	8° x 8°
10X10	10° x 10°
23X23	23° x 23°
43X43	43° x 43°
8X31	8° x 31°
10X42	10° x 42°
12X60	12° x 60°
14X100	14° x 100°
30X60	30° x 60°
60X30	60° x 30°

DIMMING	
NDIM	Non-dimmable
DALI	Dimmable - DALI
0-10V	Dimmable - 0-10V
DMX	Dimmable - DMX

GLARE PROTECTION	
OP	No glare protection
HL	Hex louver (internal)
LLO	Linear louver (internal)

FIXTURE LENGTH	
629	629 mm / 24.76 in
934	934 mm / 36.77 in
1239	1239 mm / 48.78 in

* Project-specific options are available - Please contact our Sales Representative for further information.



Lindberghstrasse 15
86343 Koenigsbrunn
Tel: +49 (0)8231/95787-0
Fax: +49 (0)8231/95787-29
www.biontechnologies.com
info@biontechnologies.com

YouTube: <http://www.youtube.com/user/BIONTECHNOLOGIES>

© 2024, BION TECHNOLOGIS GMBH
All rights reserved / Subject to change / Specifications may change without notice