



# firmus I

pureWhite | pureColor

SPECIFICATION SHEET

## BION TECHNOLOGIES GMBH

Lindberghstrasse 15  
86343 Koenigsbrunn

Tel: +49 (0)8231/95787-0  
Fax: +49 (0)8231/95787-29

[www.biontechnologies.com](http://www.biontechnologies.com)  
[info@biontechnologies.com](mailto:info@biontechnologies.com)

YouTube: <http://www.youtube.com/BIONTECHNOLOGIES>

© 2016, BION TECHNOLOGIS GMBH  
All rights reserved / Subject to change / Specifications may change without notice.

|                |                 |             |
|----------------|-----------------|-------------|
| <b>Project</b> | <b>Fixture#</b> | <b>Date</b> |
|                |                 | <b>Firm</b> |

## Ordering Information

Choose the option that suits your needs and write its corresponding code on the appropriate line to form the product code.

FIR-L- \_\_\_\_\_ - \_\_\_\_\_ - \_\_\_\_\_ - \_\_\_\_\_ - \_\_\_\_\_ - \_\_\_\_\_ - Y01

TYP - LUMINOUS COLOR
DIMMING
BEAM ANGLE
WIRING
HOUSING COLOR
WIRING CONFIGURATION
LEADERCABLE LENGTH

| TYP - LUMINOUS COLOR |                    |
|----------------------|--------------------|
| <b>PW27</b>          | pureWhite - 2700 K |
| <b>PW30</b>          | pureWhite - 3000 K |
| <b>PW35</b>          | pureWhite - 3500 K |
| <b>PW40</b>          | pureWhite - 4000 K |
| <b>PCRE</b>          | pureColor - Red    |
| <b>PCGR</b>          | pureColor - Green  |
| <b>PCBL</b>          | pureColor - Blue   |
| <b>PCAM</b>          | pureColor - Amber  |

| BEAM ANGLE    |            |
|---------------|------------|
| <b>10X10</b>  | 10° x 10°  |
| <b>22X22</b>  | 22° x 22°  |
| <b>34X34</b>  | 34° x 34°  |
| <b>60X60</b>  | 60° x 60°  |
| <b>8X31</b>   | 8° x 31°   |
| <b>10X40</b>  | 10° x 40°  |
| <b>12X60</b>  | 12° x 60°  |
| <b>14X100</b> | 14° x 100° |
| <b>30X60</b>  | 30° x 60°  |

| WIRING CONFIGURATION |                            |
|----------------------|----------------------------|
| <b>PIDX</b>          | Power IN only              |
| <b>PIDI</b>          | Power IN + Daten IN        |
| <b>PIDO</b>          | Power IN + Data IN/OUT     |
| <b>PODI</b>          | Power IN/OUT + Data IN     |
| <b>PODO</b>          | Power IN/OUT + Data IN/OUT |

| LEADERCABLE LENGTH |                                 |
|--------------------|---------------------------------|
| <b>000</b>         | no leader cable - self assembly |
| <b>006</b>         | 60 cm (23.6 in) leader cable    |
| <b>030</b>         | 3 m (118 in) leader cable       |

| DIMMING      |                  |
|--------------|------------------|
| <b>0-10V</b> | Dimmable - 0-10V |
| <b>IOT</b>   | Dimmable - IOT   |
| <b>DMX</b>   | Dimmable - DMX   |
| <b>DALI</b>  | Dimmable - DALI  |

| WIRING     |               |
|------------|---------------|
| <b>CE</b>  | Europe        |
| <b>ETL</b> | North America |

| HOUSING COLOR   |                    |
|-----------------|--------------------|
| <b>DB</b>       | DB703 powdercoated |
| <b>WH</b>       | White powdercoated |
| <b>BL</b>       | Black powdercoated |
| <b>RAL_____</b> | Custom Color RAL   |

\* Project-specific options are available - Please contact our Sales Representative for further information.