



firmus I
RGBWquad

SPECIFICATION SHEET

BION TECHNOLOGIES GMBH

Lindberghstrasse 15
86343 Koenigsbrunn

Tel: +49 (0)8231/95787-0
Fax: +49 (0)8231/95787-29

www.biontechnologies.com
info@biontechnologies.com

YouTube: <http://www.youtube.com/BIONTECHNOLOGIES>

© 2016, BION TECHNOLOGIS GMBH
All rights reserved / Subject to change / Specifications may change without notice.

Project	Fixture#	Date
		Firm

Ordering Information

Choose the option that suits your needs and write its corresponding code on the appropriate line to form the product code.

FIR-L- _____ - _____ - _____ - _____ - _____ - _____ - Y02

TYP - LUMINOUS
COLOR

TYP - LUMINOUS COLOR	
RGBW30	RGBW - 3000 K
RGBW40	RGBW - 4000 K
RGBW65	RGBW - 6500 K

DIMMING

DIMMING	
DMX	Dimmable - DMX
DALI	Dimmable - DALI
IOT	Dimmable - IOT

BEAM ANGLE

BEAM ANGLE	
10X10	10° x 10°
22X22	22° x 22°
34X34	34° x 34°
60X60	60° x 60°
8X31	8° x 31°
10X40	10° x 40°
12X60	12° x 60°
14X100	14° x 100°
30X60	30° x 60°

WIRING

WIRING	
CE	Europe
ETL	North America

HOUSING COLOR

HOUSING COLOR	
DB	DB703 powdercoated
WH	White powdercoated
BL	Black powdercoated
RAL_____	Custom Color RAL

WIRING
CONFIGURATION

WIRING CONFIGURATION	
PIDX	Power IN only
PIDI	Power IN + Daten IN
PIDO	Power IN + Data IN/OUT
PODI	Power IN/OUT + Data IN
PODO	Power IN/OUT + Data IN/OUT

LEADERCABLE
LENGTH

LEADERCABLE LENGTH	
000	no leader cable - self assembly
006	60 cm (23.6 in) leader cable
030	3 m (118 in) leader cable

Sample Order Code: FIR-L-RGBW40-IOT-34X34-CE-DB-Y02

* Project-specific options are available - Please contact our Sales Representative for further information.