



# linea xs inground hp

**RGBW**

SPECIFICATION SHEET

## BION TECHNOLOGIES GMBH

Lindberghstrasse 15  
86343 Koenigsbrunn

Tel: +49 (0)8231/95787-0  
Fax: +49 (0)8231/95787-29

[www.biontechnologies.com](http://www.biontechnologies.com)  
[info@biontechnologies.com](mailto:info@biontechnologies.com)

YouTube: <http://www.youtube.com/BIONTECHNOLOGIES>

© 2016, BION TECHNOLOGIS GMBH  
All rights reserved / Subject to change / Specifications may change without notice.

Project	Fixture#	Date
		Firm

## Ordering Information

Choose the option that suits your needs and write its corresponding code on the appropriate line to form the product code.

LIN-XS-IN-HP- \_\_\_\_\_ - DIM-DMX - \_\_\_\_\_ - \_\_\_\_\_ - \_\_\_\_\_ - Y01

TYP - LUMINOUS COLOR
DIMMING
FIXTURE LENGTH
BEAM ANGLE
GLARE PROTECTION

TYP - LUMINOUS COLOR	
RGBW22	RGBW - 2200 K
RGBW27	RGBW - 2700 K
RGBW30	RGBW - 3000 K
RGBW35	RGBW - 3500 K
RGBW40	RGBW - 4000 K
RGBW65	RGBW - 6500 K

DIMMING	
DMX	Dimmable - DMX

FIXTURE LENGTH	
629	629 mm / 24.76 in
934	934 mm / 36.77 in
1239	1239 mm / 48.78 in

BEAM ANGLE	
8X8	8° x 8°
10X10	10° x 10°
23X23	23° x 23°
43X43	43° x 43°
8X31	8° x 31°
10X42	10° x 42°
12X60	12° x 60°
14X100	14° x 100°
30X60	30° x 60°
60X30	60° x 30°

GLARE PROTECTION	
OP	No glare protection
HL	Hex louver (internal)
LL0	Linear louver (internal)

\* Project-specific options are available - Please contact our Sales Representative for further information.