



**linea xs mp**  
pureWhite | pureColor

SPECIFICATION SHEET

**BION TECHNOLOGIES GMBH**

Lindberghstrasse 15  
86343 Koenigsbrunn

Tel: +49 (0)8231/95787-0  
Fax: +49 (0)8231/95787-29

[www.biontechnologies.com](http://www.biontechnologies.com)  
[info@biontechnologies.com](mailto:info@biontechnologies.com)

YouTube: <http://www.youtube.com/BIONTECHNOLOGIES>

© 2016, BION TECHNOLOGIS GMBH  
All rights reserved / Subject to change / Specifications may change without notice.

<b>Project</b>	<b>Fixture#</b>	<b>Date</b>
		<b>Firm</b>



## Ordering Information

Choose the option that suits your needs and write its corresponding code on the appropriate line to form the product code.

LIN-XS-MP- \_\_\_\_\_ - \_\_\_\_\_ - \_\_\_\_\_ - \_\_\_\_\_ - \_\_\_\_\_ - \_\_\_\_\_ - \_\_\_\_\_ - \_\_\_\_\_ - Y01

TYP - LUMINOUS COLOR	DIMMING	FIXTURE LENGTH	BEAM ANGLE	HOUSING COLOR	GLARE PROTECTION	WIRING CONFIGURATION	LEADERCABLE LENGTH	MOUNTING OPTION
<b>TYP - LUMINOUS COLOR</b>		<b>FIXTURE LENGTH</b>		<b>HOUSING COLOR</b>		<b>LEADERCABLE LENGTH</b>		
PW22 pureWhite - 2200 K		324 324 mm / 12.76 in		AA Aluminium anodized (Standard)		ETE End to end - wiring		
PW27 pureWhite - 2700 K		477 477 mm / 18.78 in		BA Black anodized		003 + 30 cm (ca. 1 ft)		
PW30 pureWhite - 3000 K		629 629 mm / 24.76 in				006 + 60 cm (ca. 2 ft)		
PW35 pureWhite - 3500 K		782 782 mm / 30.79 in		<b>GLARE PROTECTION</b>		009 + 90 cm (ca. 3 ft)		
PW40 pureWhite - 4000 K		934 934 mm / 36.77 in		OP No glare protection		012 + 1,2 m (ca. 4 ft)		
PCRE pureColor - Red		1087 1087 mm / 42.8 in		HL Hex louver (internal)				<b>MOUNTING OPTION</b>
PCGR pureColor - Green		1239 1239 mm / 48.78 in		LL0 Linear louver (internal)				ND without bracket
PCBL pureColor - Blue								BS Universal mounting bracket
PCAM pureColor - Amber								
	<b>DIMMING</b>		<b>BEAM ANGLE</b>		<b>WIRING CONFIGURATION</b>			
	NDIM Non-dimmable		8X8 8° x 8°		IOCC IN/OUT with Connector			
	DALI Dimmable - DALI		10X10 10° x 10°		IXCX only IN with Connector			
	0-10V Dimmable - 0-10V		23X23 23° x 23°		IOOC IN open end / OUT socket			
	DMX Dimmable - DMX		43X43 43° x 43°		IOOO IN/OUT with open ends			
			8X31 8° x 31°		IXOX only IN with open ends			
			10X42 10° x 42°					
			12X60 12° x 60°					
			14X100 14° x 100°					
			30X60 30° x 60°					
			60X30 60° x 30°					

\* Project-specific options are available - Please contact our Sales Representative for further information.