



# tantulus eco indoor

pureWhite | pureColor

SPECIFICATION SHEET

## BION TECHNOLOGIES GMBH

Lindberghstrasse 15  
86343 Koenigsbrunn

Tel: +49 (0)8231/95787-0  
Fax: +49 (0)8231/95787-29

[www.biontechnologies.com](http://www.biontechnologies.com)  
[info@biontechnologies.com](mailto:info@biontechnologies.com)

YouTube: <http://www.youtube.com/BIONTECHNOLOGIES>

© 2016, BION TECHNOLOGIS GMBH  
All rights reserved / Subject to change / Specifications may change without notice.

<b>Project</b>	<b>Fixture#</b>	<b>Date</b>
		<b>Firm</b>



## Ordering Information

Choose the option that suits your needs and write its corresponding code on the appropriate line to form the product code.

TAN-IN-ECO- \_\_\_\_\_ - \_\_\_\_\_ - \_\_\_\_\_ - Y31

TYP - LUMINOUS  
COLOR

FIXTURE LENGTH

BEAM ANGLE

MOUNTING  
OPTION

TYP - LUMINOUS COLOR	
PW20	pureWhite - 2000 K
PW22	pureWhite - 2200 K
PW25	pureWhite - 2500 K
PW27	pureWhite - 2700 K
PW30	pureWhite - 3000 K
PW35	pureWhite - 3500 K
PW40	pureWhite - 4000 K
PW45	pureWhite - 4500 K
PW65	pureWhite - 6500 K
PCRE	pureColor - Red
PCGR	pureColor - Green
PCBL	pureColor - Blue

FIXTURE LENGTH	
310	310 mm / 12.2 in
615	615 mm / 24.21 in
920	920 mm / 36.22 in
1225	1225 mm / 48.23 in
1530	1530 mm / 60.24 in
1835	1835 mm / 72.24 in

BEAM ANGLE	
30X120(F)	30° x 120° frost
60X120(F)	60° x 120° frost
90X120(F)	90° x 120° frost
120X120(C)	120° x 120° clear
120X120(F)	120° x 120° frost
120X120(W)	120° x 120° white
SQR(W)	186° x 110° white

MOUNTING OPTION	
K0	Bracket Set 0°
K15	Bracket Set 15°
K30	Bracket Set 30°
K45	Bracket Set 45°
K60	Bracket Set 60°
KADJ	Positioning Hinge
Fixed Angle: Bracket count: 2 <= 1225 mm (48.23 in) > 3 HKadj: Bracket count: 2 for all lengths	

\* Project-specific options are available - Please contact our Sales Representative for further information.