



tellus m eco

pureWhite | pureColor

SPECIFICATION SHEET

BION TECHNOLOGIES GMBH

Lindberghstrasse 15
86343 Koenigsbrunn

Tel: +49 (0)8231/95787-0
Fax: +49 (0)8231/95787-29

www.biontechnologies.com
info@biontechnologies.com

YouTube: <http://www.youtube.com/BIONTECHNOLOGIES>

© 2016, BION TECHNOLOGIS GMBH
All rights reserved / Subject to change / Specifications may change without notice.

Project	Fixture#	Date
		Firm

Ordering Information

Choose the option that suits your needs and write its corresponding code on the appropriate line to form the product code.

TEL-M-ECO- _____ - _____ - _____ - _____ - _____ - Y03

TYP - LUMINOUS COLOR	DIMMING	FIXTURE LENGTH	BEAM ANGLE	WIRING	GLARE PROTECTION																																																																																						
<table border="1"> <thead> <tr> <th colspan="2">TYP - LUMINOUS COLOR</th> </tr> </thead> <tbody> <tr><td>PW27</td><td>pureWhite - 2700 K</td></tr> <tr><td>PW30</td><td>pureWhite - 3000 K</td></tr> <tr><td>PW35</td><td>pureWhite - 3500 K</td></tr> <tr><td>PW40</td><td>pureWhite - 4000 K</td></tr> <tr><td>PCRE</td><td>pureColor - Red</td></tr> <tr><td>PCGR</td><td>pureColor - Green</td></tr> <tr><td>PCBL</td><td>pureColor - Blue</td></tr> <tr><td>PCAM</td><td>pureColor - Amber</td></tr> </tbody> </table>	TYP - LUMINOUS COLOR		PW27	pureWhite - 2700 K	PW30	pureWhite - 3000 K	PW35	pureWhite - 3500 K	PW40	pureWhite - 4000 K	PCRE	pureColor - Red	PCGR	pureColor - Green	PCBL	pureColor - Blue	PCAM	pureColor - Amber	<table border="1"> <thead> <tr> <th colspan="2">DIMMING</th> </tr> </thead> <tbody> <tr><td>NDIM</td><td>Non-dimmable</td></tr> <tr><td>DALI</td><td>Dimmable - DALI</td></tr> <tr><td>DMX</td><td>Dimmable - DMX</td></tr> <tr><td>IOT</td><td>Dimmable - IOT</td></tr> <tr><td>0-10V</td><td>Dimmable - 0-10V</td></tr> </tbody> </table>	DIMMING		NDIM	Non-dimmable	DALI	Dimmable - DALI	DMX	Dimmable - DMX	IOT	Dimmable - IOT	0-10V	Dimmable - 0-10V	<table border="1"> <thead> <tr> <th colspan="2">FIXTURE LENGTH</th> </tr> </thead> <tbody> <tr><td>345</td><td>345 mm / 13.58 in</td></tr> <tr><td>650</td><td>650 mm / 25.59 in</td></tr> <tr><td>955</td><td>955 mm / 37.6 in</td></tr> <tr><td>1260</td><td>1260 mm / 49.61 in</td></tr> </tbody> </table>	FIXTURE LENGTH		345	345 mm / 13.58 in	650	650 mm / 25.59 in	955	955 mm / 37.6 in	1260	1260 mm / 49.61 in	<table border="1"> <thead> <tr> <th colspan="2">BEAM ANGLE</th> </tr> </thead> <tbody> <tr><td>8X8</td><td>8° x 8°</td></tr> <tr><td>10X10</td><td>10° x 10°</td></tr> <tr><td>23X23</td><td>23° x 23°</td></tr> <tr><td>43X43</td><td>43° x 43°</td></tr> <tr><td>52X52</td><td>52° x 52°</td></tr> <tr><td>8X31</td><td>8° x 31°</td></tr> <tr><td>10X42</td><td>10° x 42°</td></tr> <tr><td>12X60</td><td>12° x 60°</td></tr> <tr><td>14X100</td><td>14° x 100°</td></tr> <tr><td>WWW</td><td>30° x 58° (Tilt in C0-plane: -14°)</td></tr> <tr><td>WWN</td><td>30° x 11° (Tilt in C0-plane: -14°)</td></tr> <tr><td>MARKER</td><td>110° x 110° Marker</td></tr> </tbody> </table>	BEAM ANGLE		8X8	8° x 8°	10X10	10° x 10°	23X23	23° x 23°	43X43	43° x 43°	52X52	52° x 52°	8X31	8° x 31°	10X42	10° x 42°	12X60	12° x 60°	14X100	14° x 100°	WWW	30° x 58° (Tilt in C0-plane: -14°)	WWN	30° x 11° (Tilt in C0-plane: -14°)	MARKER	110° x 110° Marker	<table border="1"> <thead> <tr> <th colspan="2">WIRING</th> </tr> </thead> <tbody> <tr><td>CE</td><td>Europe</td></tr> <tr><td>ETL</td><td>North America</td></tr> </tbody> </table>	WIRING		CE	Europe	ETL	North America	<table border="1"> <thead> <tr> <th colspan="2">GLARE PROTECTION</th> </tr> </thead> <tbody> <tr><td>OP</td><td>No glare protection</td></tr> <tr><td>HL</td><td>Honeycomb louver</td></tr> <tr><td>LL17</td><td>Linear louver 17°</td></tr> <tr><td>LL00</td><td>Linear louver 0°</td></tr> <tr><td>CGC</td><td>customized glare control</td></tr> <tr><td colspan="2">Use LL17 only with beam angle www or wwn</td></tr> </tbody> </table>	GLARE PROTECTION		OP	No glare protection	HL	Honeycomb louver	LL17	Linear louver 17°	LL00	Linear louver 0°	CGC	customized glare control	Use LL17 only with beam angle www or wwn	
TYP - LUMINOUS COLOR																																																																																											
PW27	pureWhite - 2700 K																																																																																										
PW30	pureWhite - 3000 K																																																																																										
PW35	pureWhite - 3500 K																																																																																										
PW40	pureWhite - 4000 K																																																																																										
PCRE	pureColor - Red																																																																																										
PCGR	pureColor - Green																																																																																										
PCBL	pureColor - Blue																																																																																										
PCAM	pureColor - Amber																																																																																										
DIMMING																																																																																											
NDIM	Non-dimmable																																																																																										
DALI	Dimmable - DALI																																																																																										
DMX	Dimmable - DMX																																																																																										
IOT	Dimmable - IOT																																																																																										
0-10V	Dimmable - 0-10V																																																																																										
FIXTURE LENGTH																																																																																											
345	345 mm / 13.58 in																																																																																										
650	650 mm / 25.59 in																																																																																										
955	955 mm / 37.6 in																																																																																										
1260	1260 mm / 49.61 in																																																																																										
BEAM ANGLE																																																																																											
8X8	8° x 8°																																																																																										
10X10	10° x 10°																																																																																										
23X23	23° x 23°																																																																																										
43X43	43° x 43°																																																																																										
52X52	52° x 52°																																																																																										
8X31	8° x 31°																																																																																										
10X42	10° x 42°																																																																																										
12X60	12° x 60°																																																																																										
14X100	14° x 100°																																																																																										
WWW	30° x 58° (Tilt in C0-plane: -14°)																																																																																										
WWN	30° x 11° (Tilt in C0-plane: -14°)																																																																																										
MARKER	110° x 110° Marker																																																																																										
WIRING																																																																																											
CE	Europe																																																																																										
ETL	North America																																																																																										
GLARE PROTECTION																																																																																											
OP	No glare protection																																																																																										
HL	Honeycomb louver																																																																																										
LL17	Linear louver 17°																																																																																										
LL00	Linear louver 0°																																																																																										
CGC	customized glare control																																																																																										
Use LL17 only with beam angle www or wwn																																																																																											

Sample Order Code: tellus-m-eco-pCRE-ndim-3/955-52x52-Y01

* Project-specific options are available - Please contact our Sales Representative for further information.