



tellus m hpq

pureWhite

SPECIFICATION SHEET

BION TECHNOLOGIES GMBH

Lindberghstrasse 15
86343 Koenigsbrunn

Tel: +49 (0)8231/95787-0
Fax: +49 (0)8231/95787-29

www.biontechnologies.com
info@biontechnologies.com

YouTube: <http://www.youtube.com/BIONTECHNOLOGIES>

© 2016, BION TECHNOLOGIS GMBH
All rights reserved / Subject to change / Specifications may change without notice.

Project	Fixture#	Date
		Firm

Ordering Information

Choose the option that suits your needs and write its corresponding code on the appropriate line to form the product code.

TEL-M-HPQ- _____ - _____ - _____ - _____ - _____ - Y03

TYP - LUMINOUS
COLOR

DIMMING

FIXTURE LENGTH

BEAM ANGLE

WIRING

GLARE
PROTECTION

TYP - LUMINOUS COLOR	
PW27	pureWhite - 2700 K
PW30	pureWhite - 3000 K
PW35	pureWhite - 3500 K
PW40	pureWhite - 4000 K

BEAM ANGLE	
10X10	10° x 10°
22X22	22° x 22°
34X34	34° x 34°
60X60	60° x 60°
8X31	8° x 31°
10X40	10° x 40°
12X60	12° x 60°
12X90	12° x 90°
30X60	30° x 60°
WWW	30° x 58° (Tilt in C0-plane: -14°)
WWN	30° x 11° (Tilt in C0-plane: -14°)

GLARE PROTECTION	
OP	No glare protection
HL	Honeycomb louver
LL17	Linear louver 17°
LL00	Linear louver 0°
CGC	customized glare control
Use LL17 only with beam angle www or wwn	

DIMMING	
NDIM	Non-dimmable

FIXTURE LENGTH	
345	345 mm / 13.58 in
650	650 mm / 25.59 in
955	955 mm / 37.6 in
1260	1260 mm / 49.61 in

WIRING	
CE	Europe
ETL	North America

Sample Order Code: TEL-M2-HPQ-PW27-NDIM-345-34X34-HL-Y01

* Project-specific options are available - Please contact our Sales Representative for further information.