



# tellus point round xs

pureWhite

SPECIFICATION SHEET

## BION TECHNOLOGIES GMBH

Lindberghstrasse 15  
86343 Koenigsbrunn

Tel: +49 (0)8231/95787-0  
Fax: +49 (0)8231/95787-29

[www.biontechnologies.com](http://www.biontechnologies.com)  
[info@biontechnologies.com](mailto:info@biontechnologies.com)

YouTube: <http://www.youtube.com/BIONTECHNOLOGIES>

© 2016, BION TECHNOLOGIS GMBH  
All rights reserved / Subject to change / Specifications may change without notice.

<b>Project</b>	<b>Fixture#</b>	<b>Date</b>
		<b>Firm</b>

## Ordering Information

Choose the option that suits your needs and write its corresponding code on the appropriate line to form the product code.

TEL-PO-RD-XS- \_\_\_\_\_ - \_\_\_\_\_ - \_\_\_\_\_ - \_\_\_\_\_ - \_\_\_\_\_ - Y01

TYP - LUMINOUS COLOR	DIMMING	BEAM ANGLE	WIRING	GLARE PROTECTION	LEADERCABLE LENGTH																																																																												
<table style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th colspan="2" style="text-align: left; border-bottom: 1px solid black;">TYP - LUMINOUS COLOR</th> </tr> </thead> <tbody> <tr><td style="width: 10%;"><a href="#">PW27</a></td><td>pureWhite - 2700 K</td></tr> <tr><td><a href="#">PW30</a></td><td>pureWhite - 3000 K</td></tr> <tr><td><a href="#">PW35</a></td><td>pureWhite - 3500 K</td></tr> <tr><td><a href="#">PW40</a></td><td>pureWhite - 4000 K</td></tr> </tbody> </table>	TYP - LUMINOUS COLOR		<a href="#">PW27</a>	pureWhite - 2700 K	<a href="#">PW30</a>	pureWhite - 3000 K	<a href="#">PW35</a>	pureWhite - 3500 K	<a href="#">PW40</a>	pureWhite - 4000 K	<table style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th colspan="2" style="text-align: left; border-bottom: 1px solid black;">DIMMING</th> </tr> </thead> <tbody> <tr><td style="width: 10%;"><a href="#">NDIM</a></td><td>Non-dimmable</td></tr> <tr><td><a href="#">DMX</a></td><td>Dimmable - DMX</td></tr> <tr><td><a href="#">IOT</a></td><td>Dimmable - IOT</td></tr> <tr><td><a href="#">DALI</a></td><td>Dimmable - DALI</td></tr> </tbody> </table>	DIMMING		<a href="#">NDIM</a>	Non-dimmable	<a href="#">DMX</a>	Dimmable - DMX	<a href="#">IOT</a>	Dimmable - IOT	<a href="#">DALI</a>	Dimmable - DALI	<table style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th colspan="2" style="text-align: left; border-bottom: 1px solid black;">BEAM ANGLE</th> </tr> </thead> <tbody> <tr><td style="width: 10%;"><a href="#">10X10</a></td><td>10° x 10°</td></tr> <tr><td><a href="#">22X22</a></td><td>22° x 22°</td></tr> <tr><td><a href="#">34X34</a></td><td>34° x 34°</td></tr> <tr><td><a href="#">60X60</a></td><td>60° x 60°</td></tr> <tr><td><a href="#">8X31</a></td><td>8° x 31°</td></tr> <tr><td><a href="#">10X40</a></td><td>10° x 40°</td></tr> <tr><td><a href="#">12X60</a></td><td>12° x 60°</td></tr> <tr><td><a href="#">12X90</a></td><td>12° x 90°</td></tr> <tr><td><a href="#">30X60</a></td><td>30° x 60°</td></tr> <tr><td><a href="#">WWW</a></td><td>30° x 58° (Tilt in C0-plane: -14°)</td></tr> <tr><td><a href="#">WWN</a></td><td>30° x 11° (Tilt in C0-plane: -14°)</td></tr> </tbody> </table>	BEAM ANGLE		<a href="#">10X10</a>	10° x 10°	<a href="#">22X22</a>	22° x 22°	<a href="#">34X34</a>	34° x 34°	<a href="#">60X60</a>	60° x 60°	<a href="#">8X31</a>	8° x 31°	<a href="#">10X40</a>	10° x 40°	<a href="#">12X60</a>	12° x 60°	<a href="#">12X90</a>	12° x 90°	<a href="#">30X60</a>	30° x 60°	<a href="#">WWW</a>	30° x 58° (Tilt in C0-plane: -14°)	<a href="#">WWN</a>	30° x 11° (Tilt in C0-plane: -14°)	<table style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th colspan="2" style="text-align: left; border-bottom: 1px solid black;">WIRING</th> </tr> </thead> <tbody> <tr><td style="width: 10%;"><a href="#">CE</a></td><td>Europe</td></tr> <tr><td><a href="#">ETL</a></td><td>North America</td></tr> </tbody> </table>	WIRING		<a href="#">CE</a>	Europe	<a href="#">ETL</a>	North America	<table style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th colspan="2" style="text-align: left; border-bottom: 1px solid black;">GLARE PROTECTION</th> </tr> </thead> <tbody> <tr><td style="width: 10%;"><a href="#">OP</a></td><td>No glare protection</td></tr> <tr><td><a href="#">HL</a></td><td>Honeycomb louver</td></tr> <tr><td><a href="#">LL17</a></td><td>Linear louver 17°</td></tr> <tr><td><a href="#">LL00</a></td><td>Linear louver 0°</td></tr> <tr><td><a href="#">CGC</a></td><td>customized glare control</td></tr> <tr><td colspan="2"><a href="#">Use LL17 only with beam angle www or wwn</a></td></tr> </tbody> </table>	GLARE PROTECTION		<a href="#">OP</a>	No glare protection	<a href="#">HL</a>	Honeycomb louver	<a href="#">LL17</a>	Linear louver 17°	<a href="#">LL00</a>	Linear louver 0°	<a href="#">CGC</a>	customized glare control	<a href="#">Use LL17 only with beam angle www or wwn</a>		<table style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th colspan="2" style="text-align: left; border-bottom: 1px solid black;">LEADERCABLE LENGTH</th> </tr> </thead> <tbody> <tr><td style="width: 10%;"><a href="#">1M</a></td><td>1 m (3.3 ft)</td></tr> <tr><td><a href="#">3M</a></td><td>3 m (10 ft)</td></tr> <tr><td><a href="#">6M</a></td><td>6 m (19.7 ft)</td></tr> <tr><td><a href="#">9M</a></td><td>9 m (29.5 ft)</td></tr> <tr><td><a href="#">15M</a></td><td>15 m (49.2 ft)</td></tr> </tbody> </table>	LEADERCABLE LENGTH		<a href="#">1M</a>	1 m (3.3 ft)	<a href="#">3M</a>	3 m (10 ft)	<a href="#">6M</a>	6 m (19.7 ft)	<a href="#">9M</a>	9 m (29.5 ft)	<a href="#">15M</a>	15 m (49.2 ft)
TYP - LUMINOUS COLOR																																																																																	
<a href="#">PW27</a>	pureWhite - 2700 K																																																																																
<a href="#">PW30</a>	pureWhite - 3000 K																																																																																
<a href="#">PW35</a>	pureWhite - 3500 K																																																																																
<a href="#">PW40</a>	pureWhite - 4000 K																																																																																
DIMMING																																																																																	
<a href="#">NDIM</a>	Non-dimmable																																																																																
<a href="#">DMX</a>	Dimmable - DMX																																																																																
<a href="#">IOT</a>	Dimmable - IOT																																																																																
<a href="#">DALI</a>	Dimmable - DALI																																																																																
BEAM ANGLE																																																																																	
<a href="#">10X10</a>	10° x 10°																																																																																
<a href="#">22X22</a>	22° x 22°																																																																																
<a href="#">34X34</a>	34° x 34°																																																																																
<a href="#">60X60</a>	60° x 60°																																																																																
<a href="#">8X31</a>	8° x 31°																																																																																
<a href="#">10X40</a>	10° x 40°																																																																																
<a href="#">12X60</a>	12° x 60°																																																																																
<a href="#">12X90</a>	12° x 90°																																																																																
<a href="#">30X60</a>	30° x 60°																																																																																
<a href="#">WWW</a>	30° x 58° (Tilt in C0-plane: -14°)																																																																																
<a href="#">WWN</a>	30° x 11° (Tilt in C0-plane: -14°)																																																																																
WIRING																																																																																	
<a href="#">CE</a>	Europe																																																																																
<a href="#">ETL</a>	North America																																																																																
GLARE PROTECTION																																																																																	
<a href="#">OP</a>	No glare protection																																																																																
<a href="#">HL</a>	Honeycomb louver																																																																																
<a href="#">LL17</a>	Linear louver 17°																																																																																
<a href="#">LL00</a>	Linear louver 0°																																																																																
<a href="#">CGC</a>	customized glare control																																																																																
<a href="#">Use LL17 only with beam angle www or wwn</a>																																																																																	
LEADERCABLE LENGTH																																																																																	
<a href="#">1M</a>	1 m (3.3 ft)																																																																																
<a href="#">3M</a>	3 m (10 ft)																																																																																
<a href="#">6M</a>	6 m (19.7 ft)																																																																																
<a href="#">9M</a>	9 m (29.5 ft)																																																																																
<a href="#">15M</a>	15 m (49.2 ft)																																																																																

Sample Order Code: TEL-PO-RD-XS-PW27-DMX-34X34-ETL-OP-Y01

\* Project-specific options are available - Please contact our Sales Representative for further information.