



# tellus point round xs

available in **xmp** White

SPECIFICATION SHEET

## BION TECHNOLOGIES GMBH

Lindberghstrasse 15  
86343 Koenigsbrunn

Tel: +49 (0)8231/95787-0  
Fax: +49 (0)8231/95787-29

[www.biontechnologies.com](http://www.biontechnologies.com)  
[info@biontechnologies.com](mailto:info@biontechnologies.com)

YouTube: <http://www.youtube.com/BIONTECHNOLOGIES>

© 2016, BION TECHNOLOGIS GMBH  
All rights reserved / Subject to change / Specifications may change without notice.

Project	Fixture#	Date
		Firm

## Ordering Information

Choose the option that suits your needs and write its corresponding code on the appropriate line to form the product code.

TEL-PO-RD-XS-XMP- TW2740 - DIMMING - BEAM ANGLE - WIRING - GLARE PROTECTION - LEADERCABLE LENGTH - Y03

TYP - LUMINOUS COLOR	DIMMING	BEAM ANGLE	WIRING	GLARE PROTECTION	LEADERCABLE LENGTH																																																																				
<table border="1"> <tr><th colspan="2">TYP - LUMINOUS COLOR</th></tr> <tr><td>TW2740</td><td>tunableWhite - 2700 K - 4000 K</td></tr> </table>	TYP - LUMINOUS COLOR		TW2740	tunableWhite - 2700 K - 4000 K	<table border="1"> <tr><th colspan="2">DIMMING</th></tr> <tr><td>DMX</td><td>Dimmable - DMX</td></tr> <tr><td>IOT</td><td>Dimmable - IOT</td></tr> </table>	DIMMING		DMX	Dimmable - DMX	IOT	Dimmable - IOT	<table border="1"> <tr><th colspan="2">BEAM ANGLE</th></tr> <tr><td>8X8</td><td>8° x 8°</td></tr> <tr><td>10X10</td><td>10° x 10°</td></tr> <tr><td>23X23</td><td>23° x 23°</td></tr> <tr><td>43X43</td><td>43° x 43°</td></tr> <tr><td>52X52</td><td>52° x 52°</td></tr> <tr><td>8X31</td><td>8° x 31°</td></tr> <tr><td>10X42</td><td>10° x 42°</td></tr> <tr><td>12X60</td><td>12° x 60°</td></tr> <tr><td>14X100</td><td>14° x 100°</td></tr> <tr><td>WWW</td><td>30° x 58° (Tilt in C0-plane: -14°)</td></tr> <tr><td>WWN</td><td>30° x 11° (Tilt in C0-plane: -14°)</td></tr> <tr><td>MARKER</td><td>110° x 110° Marker</td></tr> </table>	BEAM ANGLE		8X8	8° x 8°	10X10	10° x 10°	23X23	23° x 23°	43X43	43° x 43°	52X52	52° x 52°	8X31	8° x 31°	10X42	10° x 42°	12X60	12° x 60°	14X100	14° x 100°	WWW	30° x 58° (Tilt in C0-plane: -14°)	WWN	30° x 11° (Tilt in C0-plane: -14°)	MARKER	110° x 110° Marker	<table border="1"> <tr><th colspan="2">WIRING</th></tr> <tr><td>CE</td><td>Europe</td></tr> <tr><td>ETL</td><td>North America</td></tr> </table>	WIRING		CE	Europe	ETL	North America	<table border="1"> <tr><th colspan="2">GLARE PROTECTION</th></tr> <tr><td>OP</td><td>No glare protection</td></tr> <tr><td>HL</td><td>Honeycomb louver</td></tr> <tr><td>LL17</td><td>Linear louver 17°</td></tr> <tr><td>LL00</td><td>Linear louver 0°</td></tr> <tr><td>CGC</td><td>customized glare control</td></tr> <tr><td colspan="2">Use LL17 only with beam angle www or wwn</td></tr> </table>	GLARE PROTECTION		OP	No glare protection	HL	Honeycomb louver	LL17	Linear louver 17°	LL00	Linear louver 0°	CGC	customized glare control	Use LL17 only with beam angle www or wwn		<table border="1"> <tr><th colspan="2">LEADERCABLE LENGTH</th></tr> <tr><td>1M</td><td>1 m (3.3 ft)</td></tr> <tr><td>3M</td><td>3 m (10 ft)</td></tr> <tr><td>6M</td><td>6 m (19.7 ft)</td></tr> <tr><td>9M</td><td>9 m (29.5 ft)</td></tr> <tr><td>15M</td><td>15 m (49.2 ft)</td></tr> </table>	LEADERCABLE LENGTH		1M	1 m (3.3 ft)	3M	3 m (10 ft)	6M	6 m (19.7 ft)	9M	9 m (29.5 ft)	15M	15 m (49.2 ft)
TYP - LUMINOUS COLOR																																																																									
TW2740	tunableWhite - 2700 K - 4000 K																																																																								
DIMMING																																																																									
DMX	Dimmable - DMX																																																																								
IOT	Dimmable - IOT																																																																								
BEAM ANGLE																																																																									
8X8	8° x 8°																																																																								
10X10	10° x 10°																																																																								
23X23	23° x 23°																																																																								
43X43	43° x 43°																																																																								
52X52	52° x 52°																																																																								
8X31	8° x 31°																																																																								
10X42	10° x 42°																																																																								
12X60	12° x 60°																																																																								
14X100	14° x 100°																																																																								
WWW	30° x 58° (Tilt in C0-plane: -14°)																																																																								
WWN	30° x 11° (Tilt in C0-plane: -14°)																																																																								
MARKER	110° x 110° Marker																																																																								
WIRING																																																																									
CE	Europe																																																																								
ETL	North America																																																																								
GLARE PROTECTION																																																																									
OP	No glare protection																																																																								
HL	Honeycomb louver																																																																								
LL17	Linear louver 17°																																																																								
LL00	Linear louver 0°																																																																								
CGC	customized glare control																																																																								
Use LL17 only with beam angle www or wwn																																																																									
LEADERCABLE LENGTH																																																																									
1M	1 m (3.3 ft)																																																																								
3M	3 m (10 ft)																																																																								
6M	6 m (19.7 ft)																																																																								
9M	9 m (29.5 ft)																																																																								
15M	15 m (49.2 ft)																																																																								

Sample Order Code: TEL-PO-RD-XMP-XS-TW2740-DMX-10X40-CE-LL00-6M-Y03

\* Project-specific options are available - Please contact our Sales Representative for further information.