



tellus point xmp

tunableWhite

SPECIFICATION SHEET

BION TECHNOLOGIES GMBH

Lindberghstrasse 15
86343 Koenigsbrunn

Tel: +49 (0)8231/95787-0
Fax: +49 (0)8231/95787-29

www.biontechnologies.com
info@biontechnologies.com

YouTube: <http://www.youtube.com/BIONTECHNOLOGIES>

© 2016, BION TECHNOLOGIS GMBH
All rights reserved / Subject to change / Specifications may change without notice.

Project	Fixture#	Date
		Firm

Ordering Information

Choose the option that suits your needs and write its corresponding code on the appropriate line to form the product code.

TEL-PO-XMP- TW3060 - - - - - - - - Y01

TYP - LUMINOUS COLOR	DIMMING	FIXTURE LENGTH	BEAM ANGLE	WIRING	GLARE PROTECTION	LEADERCABLE LENGTH																																																																														
<table style="width: 100%; border-collapse: collapse;"> <tr><th colspan="2" style="text-align: left;">TYP - LUMINOUS COLOR</th></tr> <tr><td style="width: 10%;">TW3060</td><td>tunableWhite - 3000 K - 6000 K</td></tr> </table>	TYP - LUMINOUS COLOR		TW3060	tunableWhite - 3000 K - 6000 K	<table style="width: 100%; border-collapse: collapse;"> <tr><th colspan="2" style="text-align: left;">DIMMING</th></tr> <tr><td style="width: 10%;">DMX</td><td>Dimmable - DMX</td></tr> <tr><td>DALI</td><td>Dimmable - DALI</td></tr> <tr><td>IOT</td><td>Dimmable - IOT</td></tr> </table>	DIMMING		DMX	Dimmable - DMX	DALI	Dimmable - DALI	IOT	Dimmable - IOT	<table style="width: 100%; border-collapse: collapse;"> <tr><th colspan="2" style="text-align: left;">FIXTURE LENGTH</th></tr> <tr><td style="width: 10%;">XS</td><td>110 mm / 4.33 in (XS)</td></tr> <tr><td>S</td><td>220 mm / 8.66 in (S)</td></tr> <tr><td>M</td><td>268 mm / 10.55 in (M)</td></tr> </table>	FIXTURE LENGTH		XS	110 mm / 4.33 in (XS)	S	220 mm / 8.66 in (S)	M	268 mm / 10.55 in (M)	<table style="width: 100%; border-collapse: collapse;"> <tr><th colspan="2" style="text-align: left;">BEAM ANGLE</th></tr> <tr><td style="width: 10%;">8X8</td><td>8° x 8°</td></tr> <tr><td>10X10</td><td>10° x 10°</td></tr> <tr><td>23X23</td><td>23° x 23°</td></tr> <tr><td>43X43</td><td>43° x 43°</td></tr> <tr><td>52X52</td><td>52° x 52°</td></tr> <tr><td>8X31</td><td>8° x 31°</td></tr> <tr><td>10X42</td><td>10° x 42°</td></tr> <tr><td>12X60</td><td>12° x 60°</td></tr> <tr><td>14X100</td><td>14° x 100°</td></tr> <tr><td>WWW</td><td>30° x 58° (Tilt in C0-plane: -14°)</td></tr> <tr><td>WWN</td><td>30° x 11° (Tilt in C0-plane: -14°)</td></tr> <tr><td>MARKER</td><td>110° x 110° Marker</td></tr> </table>	BEAM ANGLE		8X8	8° x 8°	10X10	10° x 10°	23X23	23° x 23°	43X43	43° x 43°	52X52	52° x 52°	8X31	8° x 31°	10X42	10° x 42°	12X60	12° x 60°	14X100	14° x 100°	WWW	30° x 58° (Tilt in C0-plane: -14°)	WWN	30° x 11° (Tilt in C0-plane: -14°)	MARKER	110° x 110° Marker	<table style="width: 100%; border-collapse: collapse;"> <tr><th colspan="2" style="text-align: left;">WIRING</th></tr> <tr><td style="width: 10%;">CE</td><td>Europe</td></tr> <tr><td>ETL</td><td>North America</td></tr> </table>	WIRING		CE	Europe	ETL	North America	<table style="width: 100%; border-collapse: collapse;"> <tr><th colspan="2" style="text-align: left;">GLARE PROTECTION</th></tr> <tr><td style="width: 10%;">OP</td><td>No glare protection</td></tr> <tr><td>HL</td><td>Honeycomb louver</td></tr> <tr><td>LL17</td><td>Linear louver 17°</td></tr> <tr><td>LL00</td><td>Linear louver 0°</td></tr> <tr><td>CGC</td><td>customized glare control</td></tr> <tr><td colspan="2">Use LL17 only with beam angle www or wwn</td></tr> </table>	GLARE PROTECTION		OP	No glare protection	HL	Honeycomb louver	LL17	Linear louver 17°	LL00	Linear louver 0°	CGC	customized glare control	Use LL17 only with beam angle www or wwn		<table style="width: 100%; border-collapse: collapse;"> <tr><th colspan="2" style="text-align: left;">LEADERCABLE LENGTH</th></tr> <tr><td style="width: 10%;">1M</td><td>1 m (3.3 ft)</td></tr> <tr><td>3M</td><td>3 m (10 ft)</td></tr> <tr><td>6M</td><td>6 m (19.7 ft)</td></tr> <tr><td>9M</td><td>9 m (29.5 ft)</td></tr> <tr><td>15M</td><td>15 m (49.2 ft)</td></tr> </table>	LEADERCABLE LENGTH		1M	1 m (3.3 ft)	3M	3 m (10 ft)	6M	6 m (19.7 ft)	9M	9 m (29.5 ft)	15M	15 m (49.2 ft)
TYP - LUMINOUS COLOR																																																																																				
TW3060	tunableWhite - 3000 K - 6000 K																																																																																			
DIMMING																																																																																				
DMX	Dimmable - DMX																																																																																			
DALI	Dimmable - DALI																																																																																			
IOT	Dimmable - IOT																																																																																			
FIXTURE LENGTH																																																																																				
XS	110 mm / 4.33 in (XS)																																																																																			
S	220 mm / 8.66 in (S)																																																																																			
M	268 mm / 10.55 in (M)																																																																																			
BEAM ANGLE																																																																																				
8X8	8° x 8°																																																																																			
10X10	10° x 10°																																																																																			
23X23	23° x 23°																																																																																			
43X43	43° x 43°																																																																																			
52X52	52° x 52°																																																																																			
8X31	8° x 31°																																																																																			
10X42	10° x 42°																																																																																			
12X60	12° x 60°																																																																																			
14X100	14° x 100°																																																																																			
WWW	30° x 58° (Tilt in C0-plane: -14°)																																																																																			
WWN	30° x 11° (Tilt in C0-plane: -14°)																																																																																			
MARKER	110° x 110° Marker																																																																																			
WIRING																																																																																				
CE	Europe																																																																																			
ETL	North America																																																																																			
GLARE PROTECTION																																																																																				
OP	No glare protection																																																																																			
HL	Honeycomb louver																																																																																			
LL17	Linear louver 17°																																																																																			
LL00	Linear louver 0°																																																																																			
CGC	customized glare control																																																																																			
Use LL17 only with beam angle www or wwn																																																																																				
LEADERCABLE LENGTH																																																																																				
1M	1 m (3.3 ft)																																																																																			
3M	3 m (10 ft)																																																																																			
6M	6 m (19.7 ft)																																																																																			
9M	9 m (29.5 ft)																																																																																			
15M	15 m (49.2 ft)																																																																																			

Sample Order Code: TEL-PO-XMP-TW3060-DALI-S-30X30-ETL-HL-3M-Y01

* Project-specific options are available - Please contact our Sales Representative for further information.