



# tellus spot

pureWhite

SPECIFICATION SHEET

## BION TECHNOLOGIES GMBH

Lindberghstrasse 15  
86343 Koenigsbrunn

Tel: +49 (0)8231/95787-0  
Fax: +49 (0)8231/95787-29

[www.biontechnologies.com](http://www.biontechnologies.com)  
[info@biontechnologies.com](mailto:info@biontechnologies.com)

YouTube: <http://www.youtube.com/BIONTECHNOLOGIES>

© 2016, BION TECHNOLOGIS GMBH  
All rights reserved / Subject to change / Specifications may change without notice.

[www.biontechnologies.com](http://www.biontechnologies.com)

<b>Project</b>	<b>Fixture#</b>	<b>Date</b>
		<b>Firm</b>



## Ordering Information

Choose the option that suits your needs and write its corresponding code on the appropriate line to form the product code.

TEL-SP- \_\_\_\_\_ - \_\_\_\_\_ - \_\_\_\_\_ - \_\_\_\_\_ - \_\_\_\_\_ - \_\_\_\_\_ - \_\_\_\_\_ - Y01

TYP - LUMINOUS COLOR	DIMMING	FIXTURE LENGTH	BEAM ANGLE	WIRING	HOUSING COLOR	GLARE PROTECTION	POSITION LEADER CABLE																																																																														
<table border="1"> <tr><th colspan="2">TYP - LUMINOUS COLOR</th></tr> <tr><td>PW27</td><td>pureWhite - 2700 K</td></tr> <tr><td>PW30</td><td>pureWhite - 3000 K</td></tr> <tr><td>PW35</td><td>pureWhite - 3500 K</td></tr> <tr><td>PW40</td><td>pureWhite - 4000 K</td></tr> </table>	TYP - LUMINOUS COLOR		PW27	pureWhite - 2700 K	PW30	pureWhite - 3000 K	PW35	pureWhite - 3500 K	PW40	pureWhite - 4000 K	<table border="1"> <tr><th colspan="2">DIMMING</th></tr> <tr><td>NDIM</td><td>Non-dimmable</td></tr> </table>	DIMMING		NDIM	Non-dimmable	<table border="1"> <tr><th colspan="2">FIXTURE LENGTH</th></tr> <tr><td>XS</td><td>117 mm / 4.61 in (XS)</td></tr> <tr><td>S</td><td>227 mm / 8.94 in (S)</td></tr> <tr><td>M</td><td>275 mm / 10.83 in (M)</td></tr> </table>	FIXTURE LENGTH		XS	117 mm / 4.61 in (XS)	S	227 mm / 8.94 in (S)	M	275 mm / 10.83 in (M)	<table border="1"> <tr><th colspan="2">BEAM ANGLE</th></tr> <tr><td>10X10</td><td>10° x 10°</td></tr> <tr><td>22X22</td><td>22° x 22°</td></tr> <tr><td>34X34</td><td>34° x 34°</td></tr> <tr><td>60X60</td><td>60° x 60°</td></tr> <tr><td>8X31</td><td>8° x 31°</td></tr> <tr><td>10X40</td><td>10° x 40°</td></tr> <tr><td>12X60</td><td>12° x 60°</td></tr> <tr><td>12X90</td><td>12° x 90°</td></tr> <tr><td>30X60</td><td>30° x 60°</td></tr> <tr><td>20X60Z10</td><td>20° x 60° (Tilt in C0-plane: 10°)</td></tr> </table>	BEAM ANGLE		10X10	10° x 10°	22X22	22° x 22°	34X34	34° x 34°	60X60	60° x 60°	8X31	8° x 31°	10X40	10° x 40°	12X60	12° x 60°	12X90	12° x 90°	30X60	30° x 60°	20X60Z10	20° x 60° (Tilt in C0-plane: 10°)	<table border="1"> <tr><th colspan="2">WIRING</th></tr> <tr><td>CE</td><td>Europe</td></tr> <tr><td>ETL</td><td>North America</td></tr> </table>	WIRING		CE	Europe	ETL	North America	<table border="1"> <tr><th colspan="2">HOUSING COLOR</th></tr> <tr><td>DB</td><td>DB703 powdercoated</td></tr> <tr><td>WH</td><td>White powdercoated</td></tr> <tr><td>BL</td><td>Black powdercoated</td></tr> <tr><td>RAL____</td><td>Custom Color RAL</td></tr> </table>	HOUSING COLOR		DB	DB703 powdercoated	WH	White powdercoated	BL	Black powdercoated	RAL____	Custom Color RAL	<table border="1"> <tr><th colspan="2">GLARE PROTECTION</th></tr> <tr><td>OP</td><td>No glare protection</td></tr> <tr><td>HL</td><td>Honeycomb louver</td></tr> <tr><td>LL00</td><td>Linear louver 0°</td></tr> <tr><td>CGC</td><td>customized glare control</td></tr> <tr><td colspan="2">Use LL17 only with beam angle www or wwn</td></tr> </table>	GLARE PROTECTION		OP	No glare protection	HL	Honeycomb louver	LL00	Linear louver 0°	CGC	customized glare control	Use LL17 only with beam angle www or wwn		<table border="1"> <tr><th colspan="2">POSITION LEADER CABLE</th></tr> <tr><td>ZS</td><td>side feed</td></tr> <tr><td>ZR</td><td>back feed</td></tr> </table>	POSITION LEADER CABLE		ZS	side feed	ZR	back feed
TYP - LUMINOUS COLOR																																																																																					
PW27	pureWhite - 2700 K																																																																																				
PW30	pureWhite - 3000 K																																																																																				
PW35	pureWhite - 3500 K																																																																																				
PW40	pureWhite - 4000 K																																																																																				
DIMMING																																																																																					
NDIM	Non-dimmable																																																																																				
FIXTURE LENGTH																																																																																					
XS	117 mm / 4.61 in (XS)																																																																																				
S	227 mm / 8.94 in (S)																																																																																				
M	275 mm / 10.83 in (M)																																																																																				
BEAM ANGLE																																																																																					
10X10	10° x 10°																																																																																				
22X22	22° x 22°																																																																																				
34X34	34° x 34°																																																																																				
60X60	60° x 60°																																																																																				
8X31	8° x 31°																																																																																				
10X40	10° x 40°																																																																																				
12X60	12° x 60°																																																																																				
12X90	12° x 90°																																																																																				
30X60	30° x 60°																																																																																				
20X60Z10	20° x 60° (Tilt in C0-plane: 10°)																																																																																				
WIRING																																																																																					
CE	Europe																																																																																				
ETL	North America																																																																																				
HOUSING COLOR																																																																																					
DB	DB703 powdercoated																																																																																				
WH	White powdercoated																																																																																				
BL	Black powdercoated																																																																																				
RAL____	Custom Color RAL																																																																																				
GLARE PROTECTION																																																																																					
OP	No glare protection																																																																																				
HL	Honeycomb louver																																																																																				
LL00	Linear louver 0°																																																																																				
CGC	customized glare control																																																																																				
Use LL17 only with beam angle www or wwn																																																																																					
POSITION LEADER CABLE																																																																																					
ZS	side feed																																																																																				
ZR	back feed																																																																																				

Sample Order Code: TEL-SP-XS-PW27-NDIM-60X60-DB-ZR-HL-Y01

\* Project-specific options are available - Please contact our Sales Representative for further information.